Cisco Catalyst 9300, Managed, L3, Full duplex, Power over Ethernet (PoE), Rack mounting, 1U

Brand: Cisco Systems Product family: Product code: C9300X-48HX-E= Product name: CATALYST 9300 48-PORT MGIG UPOE+ NETWORK ESSENTIALS



Miscellaneous	
Miscellaneous / Color Category	Gray
Miscellaneous / Compliant Standards	UL 60950-1, CAN/CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950-1, FCC CFR47 Part 15, EN 300 386 V1.6.1, EN 55032 Class A, CISPR 32 Class A, EN 61000-3-2, EN 61000-3-3, ICES-003 Class A, TCVN 7189 Class A, V-3 Class A, CISPR 35, EN 300 386, EN 55035, TCVN 7317, V-2/2015.04, V-3/2015.04, CNS 13438, KN32, KN35, RoHS

Manufacturer Warranty	
Manufacturer Warranty / Service & Support	Limited warranty - replacement - lifetime - response time: next business day ¦ Technical support - consulting - 90 days

Service & Support	
Service & Support / Type	Limited lifetime warranty

General	
General / Subtype	10 Gigabit Ethernet
General / Ports	48 x 100/1000/2.5G/5G/10GBase-T (UPOE+)
General / Compliant Standards	IEEE 802.1BA, IEEE 1588v2, IEEE 802.1ae, IEEE 802.1s, IEEE 802.1w, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ad (LACP), IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3an
General / Jumbo Frame Support	9198 bytes
General / MAC Address Table Size	32000 entries
General / Device Type	Switch - 48 ports - L3 - managed - stackable
General / Status Indicators	Status
General / Enclosure Type	Rack-mountable
General / Performance	Switching capacity: 2000 Gbps ¦ Switching capacity with stacking: 3000 Gbps ¦ Forwarding rate: 1488 Mpps ¦ Forwarding rate with stacking: 2232 Mpps
General / Features	Cisco UADP 2.0, QoS, SUDI, Cisco StackWise Technology, ZTP, Preboot Execution Environment, Cisco StackWise-1T technology, Rapid PVST+, FNF, DSCP support, SRR, CIR, mDNS, EEE, Blue Beacon LED, EVPN, PIM, VPN support, VPLS, EoMPLS, CDP, FHS, 802.1x authentication, RSPAN, LACP support, full duplex mode, PVLAN support, CoPP, SPAN

Networking	
Networking / Manageable	Yes
Networking / Form Factor	Rack-mountable
Networking / Ports Qty	48
Networking / Subcategory	Network hubs and switches
Networking / Type	Switch
Networking / Jumbo Frame Support	9198 bytes
Networking / Subtype	10 Gigabit Ethernet
Networking / Advanced Switching	Layer 3


Header	
Header / Model	9300X
Header / Product Line	Cisco Catalyst
Header / Packaged Quantity	1

Dimensions & Weight	
Dimensions & Weight / Height	1.7in
Dimensions & Weight / Width	17.5in
Dimensions & Weight / Depth	22in
Dimensions & Weight / Weight	14.59lbs


Environmental Parameters	
Environmental Parameters / Min Operating Temperature	23 °F
Environmental Parameters / Max Operating Temperature	113 °F
Environmental Parameters / Humidity Range Operating	5 - 90% (non-condensing)

Expansion / Connectivity	
Expansion / Connectivity / Interfaces	48 x 100/1000/2.5G/5G/10GBase-T RJ-45 UPOE+ - 90 W ¦ 1 x USB 2.0

Power	
Power / Voltage Required	AC 115-240 V (50 - 60 Hz)
Power / Power Device	Internal power supply - hot-plug



0889728362290



889728362290